



Mounting Suggestions

2008-2010 Harley-Davidson® Road King, Road King Classic, FLHX, FLTR, & FLHT Solo Seat

Tools Required:

- Phillips Screwdriver
- 5/8" Deep Socket or Open-End Wrench
- 7/16" Open-End Wrench

Hardware:

- Solo Seat Mounting Nuts Mustang Part#78032 or H-D equivalent (Not Included)
- Black Nylon Shoulder Washer x 2 (Included)
- 1/4" Chrome Washer x 2 (Included)



Baseplate Features:

The solo features a 16 gauge formed steel baseplate and is a direct replacement for the stock solo. The solo has a single nose clip and two chrome mounting tabs that align with the fender studs.

Stock Passenger Seat Removal Steps

1. Remove the rear fender screw.
2. Slide the passenger seat back and up.

Stock Solo Seat Removal Steps

1. Remove the solo mounting nuts located at the back of the solo seat.
2. Slide the solo back and up.

Stock One-Piece Seat Removal Steps

1. Remove the rear fender screw.
2. Remove hand strap that is secured to the motorcycle on each side of the seat where the front saddle bag mount is located.
3. Slide the stock seat back and up.

NOTE: To mount your new Mustang Solo seat you will need Seat Mounting Nuts, Mustang Part#78032 or H-D equivalent, which are not included and must be purchased separately.

Mustang Part#78032



