





Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C GLX

Silicate-free, long-life coolant TL-VW 774 F (G12+)

Description

Eurol Coolant -36 GLX has especially been developed for the new generation cooling systems of modern car engines.

Eurol Coolant -36 GLX, based on ethylene-glycol, has been approved by Volkswagen (TL 774 D) and meets the Renault D standard.

Eurol Coolant -36 GLX prevents scale forming and offers excellent protection against cavitation. Moreover, it protects all metals against corrosion, particularly aluminum and alloy irons, even at high temperatures.

Eurol Coolant -36 GLX protects against freezing up to -36 °C and contains environment-friendly additives (carboxylacids). This technology is known under the name OAT (Organic-Acid-Technology).

Eurol Coolant -36 GLX is to be used undiluted, so never top-up with pure water. Life-time of the product is 5 years or 650.000 kms for trucks or 250.000 kms for passenger cars, depending on which situation occurs

Specifications

Performance level VW TL-774 F (G12+) VW TL-774 D (G12) BS 6580 ASTM D4985 ASTM D4656 ASTM D3306 Renault Type D NATO S-759 JASO M325

first.

Eurol Coolant -36 GLX is nitrite, amine, borate, phosphate, nitrate and silicate free. The product is compatible with traditional coolants of traditional quality.

Physical properties

| Colour | Pink | |
|------------------|------------|-------------|
| Density at 20°C | 1.069 kg/l | ASTM D 1298 |
| Frost protection | -36 °C | ASTM D 1177 |

E504144 Version 1.0, 15-04-2020