



Mounting Suggestions
.....Harley-Davidson®
.....Road King® - (!&\$%&
.....FLHT/FLTR® - +!&\$%&ž
.....Screamin' Eagle 1997-20\$) &
.....FLHX 2006-20%&
.....Passenger Seat



Hardware:

- (1) Stock Rear Fender Screw
- One Black Nylon Washer x 2 (Included)
- Solo Seat Mounting Nuts Mustang Part#78032 or H-D equivalent (Not Included)

Baseplate Features:

Passenger Seats are built on 16 gauge formed steel baseplates and feature carpet and rubber bumpers to protect the fender. Rear seats have two slots in the baseplate and a chrome rear mounting tab.

Stock Passenger Seat Removal Steps

1. Remove the rear fender screw.
2. Slide the passenger seat back and up.

Mounting of Mustang Seat

1. Front of baseplate is slotted and engages into the bolts/nuts in the fender at the rear of the solo seat.
2. The supplied nylon washer goes between the rear mounting tab and the fender. Secure with stock rear fender screw.

Note: 1997-1998 models require that the black retention clip must be left in place to hold the nut insert in fender; 1997-1998 models require seat mounting bolts (Mustang part #78028) or stock Harley-Davidson®.

1999-up models: the studs in the fender have some movement to help with lining up the tabs.; 1999-up models: require Road King seat mounting nuts (Mustang part #78032 or stock H-D). (FIG. 1)

Mustang Part#78032



Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref: part#'s 75539, 75469, 75579, 75600, 76351, 75460, 75461, 75462, 79110, 79356, 79112, 79349
76693, 76695, 76721, 76723